

Fuzzy System and Performance for Fat Exposure in Milk

S.Arunanith kumar, G.Thangapandi

Final Years students, Department of Electronics and Communication Engineering

St.Joseph's College of Engineering

Old Mamallapuram Road, Semmancheri, Chennai, India

Abstract: Fuzzy based warmth controller is implemented for discovery of fat substance in cow / buffalo milk. The arrangement uses MALAB for Fuzzy Inference System (FIS) to acquire manage action and ELVIS – II+ as DAQ which acts as connection between FIS and test sample temperature organize unit. The temperature of milk model is controlled at 45°C and the fat satisfied in model is measured with the facilitate of Ultrasonic recognition method. The milk model temperature is maintained to include indistinguishable allocation of fat globules. Dissimilar cow and buffalo milk models are veteran and the outcome are compared with Gerber's process. The results seem to be superior for input milk models. In this method is used to detect the fat in ultrasonic method there is no side effect for this technique so have to improve our process in this method it is prove better efficient identical model.

Keywords: Fuzzy Inference System, Fuzzy Logic Toolbox, Ultrasound, Milk Fat.

I. INTRODUCTION

A fuzzy manage technique is a manage system based on fuzzy logic—a arithmetic scheme that analyze analog input ethics in terms of logical variables that take on nonstop ethics among 0 and 1, in distinction to usual, which operates on separate values of

moreover 1 or 0. A manage system may also have different types of control, or "ON-OFF", inputs all along with its analog inputs, and such control inputs of course will for eternity have a truth value equivalent to either 1 or 0, but the method can deal with them as simplify fuzzy functions that turn out to be whichever one value or an added. Consequently the Fuzzy Inference System can be functional to control temperature of milk model specifically.

The superiority of milk is directly related to the health of consumers. To guarantee the quality of milk and dairy products, dairy industry in several key areas such as cows scientific farming, the acquisition of raw milk, milk and dairy dispensation quality control, milk products qualified assessment, etc. need to repeatedly test the quality of exploit. There are many indicators that value the quality of milk, but the most commonly used is the main nutrients in milk – fat, protein and lactose content. Lactose substance comparatively changes less significant, while fat and protein changes spectacularly. So the principles require that the fat and protein content in exploit quality testing mandatory monitoring indicators. As for these two mechanisms in the uncovering, the traditional method is compound based, such as the fat in milk is habitually measured by Babcock technique,

Geber method, Rose-Gottlieb method and the protein satisfied measure used.

II. ULTRASONIC FAT DETECTION

Ultrasound is an oscillating sound heaviness wave with an incidence superior than the high limit of the human consideration assortment. Even though this border varies beginning individual to person, it is in the region of 20 kilohertz (20,000 hertz) in vigorous, young adults. Ultrasonic devices are worn to detect objects and determine distances. Ultrasonic imaging is used in equally veterinary medicine and individual medicine. In the nondestructive tough of products and structures, ultrasound is worn to detect indiscernible flaws. Scientifically, ultrasound is worn for attack and for amalgamation, and to raise speed element process. Animals such as bats and porpoises use ultrasound for locating prey and obstacles.

An additional important characteristic of ultrasonic measuring techniques is to facilitate, in most belongings, neither immediate nor replaceable essentials need to be supplementary to the intermediate beneath test. Ultrasonic quality parameters, rapidity and attenuation coefficient changes with the superiority of exploit. The temperature of test model has an enormous effect on exactness measure of ultrasonic parameters. Also the ultrasonic parameters locate good steadiness within 45°C to 55°C temperature assortment and it is moderately appalling when the warmth is lower than 45°C or higher than 55°C. Thus milk ultrasonic strictures decide with active heat weaken the accident of heat and makes sense reasonably accurate for amount of fat and protein pleased in milk. Using exterior Acoustic Wave devices diverse liquid

samples can be analyzed maintenance the model temperature under prohibited circumstances of 33°C.

The fat is in attendance in milk in the appearance of small globules of a mixture of diameters, from 0.15 to 15 micrometers. Milk heavy is lighter than water and creams if it is left reputation. A fat-rich deposit accumulates on the outside. Stirring and vigilant quivering restore the innovative circulation. If the layer of cream cannot be regularly scattered in this way, the milk should be slowly heated to 40°C – 50°C and gently swirled around until a homogenous fat distribution is achieved. The milk is cooled to 30°C for further process of test. The volume meters for Gerber test are calibrated at 30°C. Any distinctions in temperature will authority the capacity. Thus for strength of mind of fat satisfied in milk, the preferred milk model temperature has to be maintained. It can also be alleged that for dissimilar technique of fat recognition different warmth levels are used, which be supposed to be specifically prohibited.

III. SYSTEM OVERVIEW




Figure 1: System block diagram

The categorization put into operation mainly consist two parts: a Fuzzy Inference System (FIS) based heat control device that joystick the heat of representation and the Ultrasonic testing belongings that measures fat of model. The figure 1 depicts block diagram construction of implemented system. The warmth sensor is inserted at outlet of milk model. The ELVIS – II+ makes an analog boundary between sensor, solid state transmit and computer classification. The model test compartment is formed with 5mm diameter and detachment between Ultrasonic transducers is 110mm. A heater coil is lesion along the meeting room. To analyze and organize, the FIS based system is residential. The control signal is obtainable in the range of 3v to 8v. For solid state relay this signal is transformed in the range of 5mA – 25mA. Solid state relay operates linearly provided that output influence from 00% to 99%. The heater coil is controlled as per the illustration temperature detected originally. The milk model is tested by ultrasonic measuring instrument to get the outcome in fat.

IV. FUZZY INFERENCE SYSTEM

Fuzzy deduction scheme have been productively efficient in pasture such as automatic be in charge of, data understanding, choice study, specialist scheme, and processor vision. for the reason that of its various environment, fuzzy deduction systems are connected with a number of names, such as fuzzy-rule-based scheme, fuzzy expert systems, fuzzy modeling, fuzzy associative remembrance, fuzzy logic controllers, and on the whole fuzzy systems. Because the terms used to express the various parts of the fuzzy implication process are far from average, we will try to be as

clear as promising about the different terms introduced in this section.

Fuzzy logic, which is the logic on which fuzzy put in order is based, is much faster in spirit to human thinking and normal language than the conservative logical systems. It provides a successful means of capturing the estimated, imprecise nature of the real humanity. The indispensable ingredient of the fuzzy logic controller (FLC) is a set of linguistic control rules interrelated by the twin concepts of fuzzy allegation and the compositional rule of presumption. In quintessence, then, the FLC provides an algorithm which can exchange the linguistic organize strategy based on expert familiarity into a mechanical control approach. The methodology of the FLC appears exceedingly functional what time the processes are too composite for examination by conformist quantitative techniques or when the available sources of in sequence are interpreted qualitatively, inaccurately, or uncertainly. Thus fuzzy logic put in order may be observation as a step toward a rapprochement between traditional precise arithmetic manages and human-like statement making.

Fuzzy controllers are worn were organize action is computed by revenue of fuzzy logic operations. It receives crisp data from the data achievement system and transfer control or references to manipulated variables. In this case, the input and output patchy, the decision / control levels, and the organizer stream diagram involving are defined as the implicated variables. The controller acquaintance includes linguistic variable (LV), set of the regulations, the interpretation period, and the way

of the management the corporeal data, the fuzzy logic procedure, and the defuzzification scheme. The submission such as water shower temperature organize, temperature control of polymerization response, solar air conditioning system, approximation heat tolerance of plants by chlorophyll fluorescence dimension, accomplishment of fuzzy logic system based on FPGA using VHDL, educational brightness tracking system, petroleum severance process, fluid level organize system with SCADA , refrigeration plant and numerous more are originate to be giving expensive outcome for Fuzzy Logic Controllers (FLC) as compared to conformist controllers that hardened. Fuzzy logic is the logic on which fuzzy control is based, is much quicker in spirit to human accepted wisdom and natural language than the usual logical systems.

V. EXPERIMENTAL RESULTS

The four milk samples are selected having different fat concentration directly from farm. From each sample 30ml of milk is taken for testing which will be heated up to 45°C exactly. The milk in the specimen bottle is thoroughly mixed through gentle shaking. This is done to bring about an even allocation of fat and to check frothing and arrangement of butter. Milk is lighter than water and creams if it is left reputation. A fat-rich layer accumulates on the exterior. Emotive and careful quivering restores the innovative allocation. The prepared sample is sucked to difficult chamber that is warmth prohibited. Fuzzy Inference System detects the preliminary temperature of milk model and compares with set point (45°C). According to the error generated the first iteration output is fired by means of fault FIS file. Therefore, once the accurate

temperature is achieved the fat content in model is measured. The ultrasound is passionate instantly and the velocity of milk lessening coefficient is calculated.

Table 1 shows the resulting values indicated by Ultrasonic apparatus where dwindling of signal is calculated. The model is tested frequently to get accurate value of fat stuffing in given milk model.

Sample Number	Fat Contents (No of Repetitions)			
	1	2	3	4
1	5.25	6.20	6.19	6.30
2	2.19	2.15	2.09	2.18
3	4.51	4.45	4.48	4.54
4	3.79	3.71	3.74	3.79

Table 1: The values of Fat contents in different milk sample.

VI. CONCLUSION

Fat globules satisfied in milk basically depend on model temperature. The fat globules can be regularly disseminated with augment in warmth of illustration. The Fuzzy Logic controller is practical to specifically organize the temperature of milk section. System is successful to indicate accurate value of fat stuffing in milk taster, maintenance constant the temperature of model each instance it is weathered. Consequently to perceive fat comfortable in milk, the sample temperature can be prohibited by Fuzzy Logic type temperature regulator procedure. The faltering block in system is time enthusiastic for heating model temperature, as it take many seconds to achieve the preferred set point. This problem may be rectified in future learning to reduce the time utilization. In this process we have examine the full expansion about the fuzzy system and their performance based on fat

exposure to the milk content. It is a main advantage for the specific data and the produced.

REFERENCES

- [1] Amit Salunkhe, Mahesh Chavan, Implementation of Fuzzy System for Fat detection in milk, International Journal of Advanced Research in Electrical, Electronics and Instrumentation Engineering , Vol. 2, Issue 6, June 2013.
- [2] Anwar Sadat & Pallavi Gupta, "Acoustic Attenuation Technique for the Detection of Adulteration in Milk", International Journal of Computer Applications on Electronics, No. 02, Dec 2011.
- [3] Xuan Sun, Changsheng Ai, Yuzhen Ma, "Milk Quality Automation Detecting Technology Based on Dynamic Temperature", IEEE Chinese Control and Decision Conference (CCDC) May-2008.
- [4] Marina Cole, Gurmukh S. Sehra etc., "Fabrication and Testing of Smart Tongue Devices for Liquid Sensing", IEEE Transactions On Fuzzy Systems Jan 2002.
- [5] Qi Xin, Hou Zhi Ling, Tian Jian Long, Yu Zhu, "The rapid determination of fat and protein content in fresh raw milk using the laser light scattering technology", Optics and Lasers in Engineering 44 pp-858-869 Apr. 2006.
- [7] Ekaterina A. Skiba, Vladimir N. Khmelev, "Sterilization of Milk by Ultrasonics", 8th International Siberian Workshop and Tutorials Edm'2007, Session V, July 1-5, Erlagol.
- [8] Chuen Chien Lee, "Fuzzy Logic in Control Systems: Fuzzy Logic Controller-Part I", 11th Transactions on Systems Man, vol. 20. No. 2. March/April. 1990.
- [9] Ahmad Johan Mahbob, Mahanijah Md Kamal and Faieza Hanum Yahaya, "Water Temperature Using Fuzzy Logic", 2009 5th International Colloquium on Signal Processing & Its Applications (CSPA), Apr. 2009.
- [10] A.M.F. Fileti, A.J.B. Antunes, F.V. Silva and V. Silveira Jr, "Experimental investigations on fuzzy logic for process control", Control Engineering Practice 15 (2007) 1149-1160.
- [11] Zhen Lu, Jili Zhang, Yongpan Chen and Tianyi Zhao, "Fuzzy control model and simulation of supply air system in a test rig of low-temperature hot water radiator system", Energy and Buildings 42 pp 386-392 May 2010.